



CENTRAL ASIAN JOURNAL OF THEORETICAL AND APPLIED SCIENCES

Volume: 04 Issue: 05 | May 2023 ISSN: 2660-5317
<https://cajotas.centralasianstudies.org>

Methods of Manufacturing Models From Polystyrene Foam.

Qosimova Zamira Medatovna

Senior Lecturer of the Department of Mechanical Engineering and Automation, Fergana polytechnic institute, Fergana, Uzbekistan

Uraimov Mukhammaddiyor Bahodir ogli

Fergana polytechnic institute, 3rd year student

Received 24th Mar 2023, Accepted 13th Apr 2023, Online 6nd May 2023

Abstract: *This article discusses methods for manufacturing models from expanded polystyrene, in a foundry production. An analysis is made of the advantages and disadvantages of each method, taking into account the overall dimensions, types of production, and the quality of the resulting castings.*

Key words: *casting, expanded polystyrene, molds, flasks, burnt out models, thermal destruction, evacuation, ferromagnetic material.*

Methods for manufacturing models from polystyrene foam in foundry production are associated with the improvement of existing technological processes and the development of fundamentally new special casting methods. One of the most important issues is the choice of the optimal casting manufacturing technology. It is necessary to pay attention not only to ensuring special requirements for the quality of the resulting castings, high physical, mechanical and operational properties, but also to the technical and economic indicators of the technology for manufacturing castings, including machining.

A model made of polystyrene can be made in molds, as well as cut out of polystyrene foam. In the manufacture of models in molds, expandable polystyrene is used as the starting material, which is supplied in granular form. For foundry production, special grades of foundry polystyrene foam are produced. Under the influence of heat, the granules foam, increasing in volume by 5...7 times. The calculated amount of granulated polystyrene is poured into the mold and steam is supplied. Polystyrene foams, increasing in size, and occupies the volume of the mold. Machines are made for the production of models from expandable polystyrene. This technology for obtaining models is acceptable in the mass production of castings. But it is possible to produce casting according to burnt-out models in a single production. In this case, the model must be made from foam by cutting, and the mold must be made in flasks using conventional sand. To improve the quality of the surface of the future casting, the model is painted.

In this way it is possible to obtain castings without cores, without slopes, without bays and seams with tighter dimensional tolerances and with reduced machining allowances compared to sand casting on wooden or metal models.

The method of casting on burnt-out models allows the use of dry sand for the mold, which reduces the complexity of the process. In this case, vacuum molding can be used, which ensures the retention of sand and the removal of thermal degradation products.

The use of bulk ferromagnetic material, shot or metal sand instead of dry sand allows the use of a magnetic field to hold the mold during the pouring of metal. However, the interaction of the molten metal with the destruction products of the material of the model often leads to the appearance of specific defects in castings: surface shells (due to the deposition of solid carbon); gas sinks; waviness of the surface of castings, etc. The quality of the surface of castings essentially depends on the properties of the material of the model, in particular, its specific gravity. With a decrease in the specific gravity of the material, the amount of degradation products decreases, but the rigidity and strength of the model decrease, which increases the likelihood of deformation when using compacted sand-clay mixtures.

The possibility of obtaining castings in molds from dry sand without a binder is explained by various researchers in different ways. On the one hand, it is believed that the form of dry sand acquires strength due to the binding action of the products of evaporation of expanded polystyrene condensed in the pores of the form, which are formed during its gasification. On the other hand, the binding effect of condensation products is denied and it is argued that the stability of dry sand molds and the possibility of forming castings in them is explained by the replacement of the model by the melt. However, a number of researchers have found that a gap between the model and the melt is formed, and its value depends on the temperature of the melt, pouring speed, hydrostatic head, and other factors. It is believed that the main factor that keeps the sand in a stable position is the action of the filtration forces of the gas flow, which is formed as a result of the interaction of the model material and the melt.

In the manufacture of castings in molds from dry quartz sand without a binder, due to the discrepancy between the dimensions of the casting and the model, sand blockages are formed. A significant number of castings are rejected. The application of a strong and gas-permeable paint to the polystyrene foam model, which stabilizes the molds from bulk material until the formation of a hardened casting crust, made it possible to reduce the production of defective castings.

The method of casting into magnetic molds for burnt models. The polystyrene foam model is covered with a ferromagnetic molding material, on which a magnetic field is applied. Under the action of a magnetic field, the particles of a ferromagnetic material are bound into a single whole. Filling is carried out as usual. After the magnetic field is removed, the molding material is poured out of the flask. This method of obtaining castings retains the main advantages of casting into molds from dry quartz sand and at the same time eliminates their main disadvantage - the formation of blockages. However, this method has found application for producing castings of relatively small mass and simple configuration. The greatest compaction is received by the mold material located at the walls, which extend along the magnetic lines. Therefore, for casting massive and complex castings, a high magnetic field strength is required, which requires very large magnets to create.

References:

1. Литье по выжигаемым моделям: Учебное пособие литейное производство черных и цветных металлов // Сост. В.М. Григорьев. — Хабаровск: Изд-во Хабар. гос. техн. ун-та, 2002.
2. Casting on burnt models: Textbook for foundry production of ferrous and non-ferrous metals // V.M. Grigoriev. - Khabarovsk, 2002.
3. Bahodir o'g'li, U. M. (2022). Calculation of Tolerances of Landings with A Gap by Software. *Eurasian Scientific Herald*, 8, 170-175.
4. Косимова, З. М. (2022). Анализ Измерительной Системы Через Количественное Выражение Ее Характеристик. *Central Asian Journal of Theoretical and Applied Science*, 3(5), 76-84.
5. Рубидинов, Ш. Ф. У., Қосимова, З. М., Файратов, Ж. Ф. У., & Акрамов, М. М. Ў. (2022). МАТЕРИАЛЫ ТРИБОТЕХНИЧЕСКОГО НАЗНАЧЕНИЯ ЭРОЗИОННЫЙ ИЗНОС. *Scientific progress*, 3(1), 480-486.
6. Косимова, З. М., Мамуров, Э. Т., & угли Толипов, А. Н. (2021). Повышение эффективности средств измерения при помощи расчетно-аналитического метода измерительной системы. *Science and Education*, 2(5), 435-440.
7. Qosimova, Z. M., & RubidinovSh, G. (2021). Influence of The Design of The Rolling Roller on The Quality of The Surface Layer During Plastic Deformation on the Workpiece. *International Journal of Human Computing Studies*, 3(2), 257-263.
8. Мамуров, Э. Т., Косимова, З. М., & Собиров, С. С. (2021). Разработка технологического процесса с использованием cad-cam программ. *Scientific progress*, 2(1), 574-578.
9. Мамуров, Э. Т., Косимова, З. М., & Джемилов, Д. И. (2021). Повышение производительности станков с числовым программным управлением в машиностроении. *Science and Education*, 2(5), 454-458.
10. Косимова, З. М., & Акрамов, М. М. Ў. (2021). Технологические особенности изготовления поршней. *Scientific progress*, 2(6), 1233-1240.
11. Мамуров, Э. Т., Косимова, З. М., & Гильванов, Р. Р. (2021). Использование программ для расчетов основного технологического времени. *Scientific progress*, 2(1), 918-923.
12. Medatovna, K. Z., & Igorevich, D. D. (2021). Welding Equipment Modernization. *International Journal of Human Computing Studies*, 3(3), 10-13.
13. Қосимова, З., Акрамов, М., Рубидинов, Ш., Омонов, А., Олимов, А., & Юнусов, М. (2021). ТОЧНОСТЬ ИЗГОТОВЛЕНИЯ ПОРШНЕЙ В ЗАВИСИМОСТИ ОТ ВЫБОРА ЗАГОТОВКИ. *Oriental renaissance: Innovative, educational, natural and social sciences*, 1(11), 418-426.
14. Shoxrux G'ayratjon o'g, R., Oybek o'g'li, O., & Bahodirjon o'g'li, L. A. (2022). Effect of Using Rolling Material in the Manufacture of Machine Parts. *Central Asian Journal of Theoretical and Applied Science*, 3(12), 137-145.
15. O'G, R. S. G. A., Obidjonovich, T. F., Oybek O'g'li, O. A., & Bahodirjon O'g'li, L. A. (2023). ANALYSIS OF THE MILLING PROCESSING PROCESS ON THE SHAPED SURFACES OF STAMP MOLDS. *European International Journal of Multidisciplinary Research and Management Studies*, 3(04), 124-131.

16. Шохрух, Г. У. Р., & Гайратов, Ж. Г. У. (2022). Анализ теории разъемов, используемых в процессе подключения радиаторов автомобиля. *Science and Education*, 3(9), 162-167.
17. Ruzaliyev, X. S. (2022). Analysis of the Methods of Covering the Working Surfaces of the Parts with Vacuum Ion-Plasmas and the Change of Surface Layers. *Eurasian Scientific Herald*, 9, 27-32.
18. Teshaboyev, A. M., & Meliboyev, I. A. (2022). Types and Applications of Corrosion-Resistant Metals. *Central Asian Journal of Theoretical and Applied Science*, 3(5), 15-22.
19. Mamirov, A. R., Rubidinov, S. G., & Gayratov, J. G. (2022). Influence and Effectiveness of Lubricants on Friction on the Surface of Materials. *Central Asian Journal of Theoretical and Applied Science*, 3(4), 83-89.
20. O'g, R. S. G. A. (2022). Classification of Wear of Materials Under Conditions of High Pressures and Shock Loads.
21. Nomanjonov, S., Rustamov, M., Sh, R., & Akramov, M. (2019). STAMP DESIGN. *Экономика и социум*, (12 (67)), 101-104.
22. Рубидинов, Ш. Ф. Ў. (2021). Бикрлиги паст валларга совук ишлов бериш усули. *Scientific progress*, 1(6), 413-417.
23. Рубидинов, Ш. Ф. Ў., & Гайратов, Ж. Г. У. (2021). Штампларни таъмирлашда замонавий технология хромлаш усулидан фойдаланиш. *Scientific progress*, 2(5), 469-473.
24. Рубидинов, Ш. Г. У., & Гайратов, Ж. Г. У. (2021). Кўп операцияли фрезалаб ишлов бериш марказининг тана деталларига ишлов беришдаги унумдорлигини тахлили. *Oriental renaissance: Innovative, educational, natural and social sciences*, 1(9), 759-765.
25. Oybek o'g'li, O. A., & Bahodirjon o'g'li, L. A. (2023). Development of Technology for the Manufacture of Porous Permeable Materials with Anisotropic Pore Structure by Vibration Molding. *CENTRAL ASIAN JOURNAL OF MATHEMATICAL THEORY AND COMPUTER SCIENCES*, 4(2), 89-94.
26. Тураев, Т. Т., Топволдиев, А. А., Рубидинов, Ш. Ф., & Жайратов, Ж. Г. (2021). Параметры и характеристики шероховатости поверхности. *Oriental renaissance: Innovative, educational, natural and social sciences*, 1(11), 124-132.
27. Рустамов, М. А. (2021). Методы термической обработки для повышения прочности зубчатых колес. *Scientific progress*, 2(6), 721-728.
28. Файзиматов, Ш. Н., & Рустамов, М. А. (2018). Аэродинамический эффект для автоматизации процесса перекачки химических агрессивных реагентов. *Современные исследования*, (6), 112-115.
29. Akbaraliyevich, R. M. (2022). Improving the Accuracy and Efficiency of the Production of Gears using Gas Vacuum Cementation with Gas Quenching under Pressure. *Central Asian Journal of Theoretical and Applied Science*, 3(5), 85-99.
30. Файзимтов, Ш. Н., & Рустамов, М. А. (2017). ПРИМЕНЕНИЕ ПРОГРЕССИВНЫХ МЕТОДОВ ДЛЯ ОРИЕНТАЦИИ И УСТАНОВКИ ЗАКЛЕПОК В ОТВЕРСТИЕ С ГОРИЗОНТАЛЬНОЙ ОСЬЮ. In *НАУЧНЫЙ ПОИСК В СОВРЕМЕННОМ МИРЕ* (pp. 44-45).
31. Таджибаев, Р. К., Гайназаров, А. А., & Турсунов, Ш. Т. (2021). Причины Образования Мелких (Точечных) Оптических Искажений На Ветровых Стеклах И Метод Их Устранения. *Central Asian Journal of Theoretical and Applied Science*, 2(11), 168-177.

32. Гайназаров, А. Т., & Абдурахмонов, С. М. (2021). Системы обработки результатов научных экспериментов. *Scientific progress*, 2(6), 134-141.
33. Таджибаев, Р. К., Турсунов, Ш. Т., & Гайназаров, А. А. (2022). Повышения качества трафаретных форм применением косвенного способа изготовления. *Science and Education*, 3(11), 532-539.
34. Таджибаев, Р. К., Турсунов, Ш. Т., Гайназаров, А. А., & Сайфиев, Б. Х. (2023). КОНТРАФАКТНАЯ ПРОДУКЦИЯ. ДЕШЕВАЯ ПРОДУКЦИЯ ИЛИ ГАРАНТИЯ БЕЗОПАСНОСТИ. *CENTRAL ASIAN JOURNAL OF MATHEMATICAL THEORY AND COMPUTER SCIENCES*, 4(2), 81-88.
35. Gaynazarov, A. T., & Rayimjonovich, A. R. (2021). ТЕОРЕТИЧЕСКИЕ ОСНОВЫ РАЗРАБОТКИ КЛЕЯ В ПРОЦЕССЕ СВАРКИ НА ОСНОВЕ ЭПОКСИДНОГО СПЛАВА ДЛЯ РЕМОНТА РЕЗЕРВУАРОВ РАДИАТОРА. *Oriental renaissance: Innovative, educational, natural and social sciences*, 1(10), 659-670.
36. Акрамов, М. М. (2022). Краткая Характеристика Горячих Цинковых Покровтий. *Central Asian Journal of Theoretical and Applied Science*, 3(5), 232-237.
37. Akramov, M. M. (2021). Metallarni korroziyalanishi va ularni oldini olish samarodorigi. *Scientific progress*, 2(2), 670-675.
38. Акрамов, М. М. (2021). ДЕТАЛЛАРНИНГ ЮЗАЛАРИНИ КИМЁВИЙ-ТЕРМИК ИШЛОВ БЕРИШГА ҚАРАТИЛГАН ТАКЛИФЛАР. *Scientific progress*, 2(6), 123-128.
39. Акрамов, М. М. (2021). Повышение физико-механических свойств стальных деталей при пластической деформационной обработке. *Scientific progress*, 2(6), 129-133.
40. Akramov, M., Rubidinov, S., & Dumanov, R. (2021). METALL YUZASINI KOROZIYABARDOSH QOPLAMALAR BILAN QOPLASHDA KIMYOVIY-TERMIK ISHLOV BERISH ANAMIYATI. *Oriental renaissance: Innovative, educational, natural and social sciences*, 1(10), 494-501.
41. Таджибаев, Р. К. (2022). МОДЕРНИЗАЦИЯ ТОКАРНО-ВИНТОРЕЗНОГО СТАНКА МОДЕЛИ ДИП-500 ДЛЯ ПОВЫШЕНИЯ ВОЗМОЖНОСТЕЙ (ГАБАРИТОВ) ОБРАБОТКИ ДЕТАЛЕЙ ДО ВОЗМОЖНОСТЕЙ СТАНКА МОДЕЛИ ДИП-800. *Universum: технические науки*, (7-1 (100)), 35-39.